

## PLASThick DELIVERY PROGRAMME

- Extruded foam PVC sheets.
- Semi-celuka production technology through a multi-channel die.
- Smooth surface for direct printing.
- High rigidity and even cells.
- Optimum whiteness.
- Application for signage, display, kitchen and bathroom cabinets, interior decoration, exhibit booth.

### PLASThick

Thickness	1560x3050 mm
8 mm	√
10 mm	√
15 mm	√
19 mm	√

### WHITE COLOUR VALUES

Colour	Min	Max.
L	89	92
a	+0,40	+0,90
b	-2,55	-4,10

### HARDNESS

Thickness	Shore-G Hardness
8-10	54 Shore-D ±0,03
15	60 Shore-D ±0,03
19	66 Shore-D ±0,03

### PALLET QUANTITIES

Thickness	1560x3050 Sheet / Pallet
8 mm	50
10 mm	40
15 mm	30
19 mm	25

### TOLERANCE IN THICKNESS

- +/- 0.30 mm for 8 & 10 mm
- +/- 0.40 mm for 15 mm
- +/- 0.50 mm for 19 mm
- Rectangularity is max 7 mm per sheet

### TOLERANCE IN SIZE

- 0 to + 7 mm on length
- 0 to + 2 mm on width
- Rectangularity is max 7 mm per meter
- \* Tolerances refer to online cutting

### DENSITY

0,50gr/cm <sup>3</sup>	±0,03gr/cm <sup>3</sup>
------------------------	-------------------------

